

THE CELEBRATED HERITAGE

60 years have passed since the rise of the icon in the Cub category. It was a heritage we all knew, sold for over 100 million units. Everything about it was to provide the joy in people's lives. Now, it is making a comeback with the same reliability and frugality to create the next chapter in its long history.



The very first Super Cub C100 was introduced in 1958.



INNOVATION THAT STARTS IT ALL C125

The technology was legendary then, loved for its youthful soul. Making a comeback, the innovation has been remastered for a whole new generation. It is contemporary now, expected by the free-spirited.



TIMELESS DESIGN FOR THE AUTHENTIC SOUL

Up until now, the design has always been head-turning to those who are fond of retro-inspired machinery. There is a clean, high-quality feel to the smallest details of all parts. Once you ride it, you will know it.



Honda SMART KEY SYSTEM

SPECIFICATION

Dimension

Overall (L x W x H) : 1.910 x 718 x 1.002 mm
Wheelbase : 1.243 mm
Ground Clearance : 136 mm
Fuel Tank Capacity : 3,7 liter
Seat Height : 780 mm
Curb Mass : 107 kg

Engine

Engine Type : Air Cooled, SOHC 4 Stroke
Displacement : 124,89 cm³

Bore x Stroke : 52,4 x 57,913 mm
Compression Ratio : 9,3 : 1
Maximum Power : 6,76 kW / 7.500 rpm
Maximum Torque : 9,79 Nm / 5.000 rpm
Transmission : Manual, 4 - speed
Clutch System : Wet, Multiple With Coil Spring
Oil Capacity : 0,8 L (Periodic Exchange)

Frame

Front Tire Size : 70/90-17 M/C 38P (Tubeless)
Rear Tire Size : 80/90-17 M/C 50P (Tubeless)
Front Brake : Hydraulic Disc

Rear Brake : Mechanical Leading Trailing
Frame Type : Back Bone, Steel
Front Suspension Type : Telescopic Front Suspension
Rear Suspension Type : Twin Rear Suspension

Electrical

Ignition Type : Full Transistorized, Battery
Battery : 12 V - 3 Ah, MF-Wet Type
Spark Plug Type : NGK CPR6EA-9 / DENSO U20EPR9

Specification of the product is subject to change without notice for the product improvements.



Pearl Shining Black



Pearl Niltave Blue



Pearl Nebula Red



THE ONE AND ORIGINAL

